

7X3 Specs

Mounted on Flatbed or Service Body

Standard Features

- 21,000 lb. Hook load on 3-part line (Block NOT included)
- Variable Speed Main & Sand line
- Main & Sand line along with structure are tested and certified with Dynamometer
- NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/7,000 lbs.
 - Supplied with 250' of 7/16" cable & 5t hook
- 40 ft hydraulically extending MAST
 - Optional Extension up to 48'
- Standard 20 ft aluminum pipe racks with pipe securing winches
 - Hydraulic lowering option available
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 12' Diamond Plate Flatbed
- Custom Headache rack above deck
- 50 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 1000 lb. -- holds 1000' of 3/8" Cable
 - 1500 lb. -- holds 1500' of 3/8" Cable
 - 2500 lb. -- holds 2000' of 3/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Hybrid Option Available
- Front Outrigger & Wire Winder options
- 3 Part block and 12 Ton Hook