

# 20X3 Specs

## Mounted on Flatbed

### Standard Features

- 60,000 lb. Hook load on 3-part block
  - Variable Speed Main & Sand line
  - Main & Sand line along with structure are tested and certified with Dynamometer
  - NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/20,000 lbs.
  - Supplied with 250' of 5/8" cable & 10t hook
- 53 ft hydraulically extending MAST
  - 51' of True Hook Height
  - Hydraulic extension by dual 15' Stroke Cylinders
- 4 Hydraulic Outriggers with 24" stroke 12" base
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 16' Diamond Plate Flatbed
- Custom Headache rack above deck
- 85 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint
- 3-Part Block

### Additional Options

- Sand Line Options -- All 550 fpm bare drum
  - 3500 lb. -- holds 2500' of 1/2" Cable
  - 5000 lb. -- holds 3500' of 1/2" Cable
  - 8000 lb. -- holds 4000' of 5/8" Cable
  - Adjustable speed settings
  - Available counter that shows DEPTH in INCHES
- Layout Line winches -- available on driver and/or passenger side
  - 250 fpm/2000 lb. -- 150' 3/8" Cabel
- Electric over Hydraulic Upgrade
  - Electronic oil pressure gauge
  - Electronic oil temperature
  - Electronic oil filter service indicator
  - Weight Load Indicator in LBS.
  - Wireless Remote
    - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
  - Sealed airtight with locks
- GETEC Hydraulic Generator
  - 120V/14,000 Watts
- Hydraulic Air Compressor
  - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Cathead with rollers
- Sargent GEN 2 Spinner
  - 2-12" Pipe
  - Heavy Duty Clamp